

AMYTEL[®] DECT Conference Phone WCP-1000.24

- the Wireless, Cord-free, High-performance Conference Phone

Completely wireless, the Amytel DECT Conference Phone has been specifically created to allow you to hold two-way conference calls anywhere, anytime. Better still, it uses unique, advanced patented technology to deliver high-quality sound that is crisp and clear.

- * **Medium to large Conf. Room**
- Up to 20 persons
- * **Wireless**
- * **Portable and versatile**
- * **Outstanding performance**
- * **Crystal-clear audio quality**
- * **Ergonomic and stylish design**



Key Features

Pod :

Radio Frequency

Digital signal processing (DSP) operation

Voice encryption for maximum security

Out-of-range warning

Audio

Full-duplex speakerphone

360 degree microphone pick-up with 3 microphones

Patented DSP echo-cancellation technology

Voice encryption for maximum security

User Interface

Liquid crystal display

Call elapse time display

Battery remaining talk time display

3 dual colour LEDs indicate status

Phonebook dialling

Digital voice volume control

5 ringer melodies

Telephone

Tone dialling

Last number redial

Mute function

Compatible with analogue PBX

User phone number programming and display

Power System

User-replaceable rechargeable battery pack

Up to 80 hours standby time and 10 hours talk time

Auto standby power-saving mode

Low battery warning

Base :

Base page to Pod

Audio jack (2.5 mm). Connects to optional recording device

Modular connection

AC power adapter

Technical Specifications

Radio frequency : 2.4GHz DECT

Speaker volume : 90 dBspl A weighted

Speaker frequency response : 200-38000kHz

Record output : Phone, -10dBu nominal

Impedance : < 1000 ohms

Dynamic range : 60 dB THD < .01%

Echo-cancellation tail time : 60 mS x 3

Noise-cancellation attenuation : 12 dB

Convergence rate : 5 - 10 seconds

Dimensions

Pod : D 265 x H 47 mm

Base : W 122 x H 134 x D 67 mm

Weight

Pod : 2.1 kg (with battery)

Base : 1.07 kg

Power

Pod : Rechargeable Ni-MH, 1800mAh

Base : Input AC 240V 50Hz

: Output DC 12V 500mA

Sole Agent :

